

Rugged & Professional

RP1000

〈Real size〉



Physical Characteristics		
Dimensions (WxHxD)	73 x 135 x 21.5mm	
Weight	250 g	
Display	3.5" QVGA TFT Touch LCD with Backlight (VGA optional)	
Keypad	Front : 8 keys and Navigation key, Side : 4 function keys	
Memory Expansion Slot	HC Micro SD slot (up to 16GB)	
Battery	Standard : 3.7V 1860mAh, Extended : 3.7V 3600mAh Built-in Backup Battery 200mAh	
Notification	LED and Vibration	
Interface	USB Host 1.1, USB Client 2.0, External Serial RS232C	
Audio	Dual Speaker, Receiver, Mic.	
Performance		
Operating System	Window Mobile 6.5 Professional	
CPU	PXA320 806MHz	
Memory	128MB RAM / 256MB and 512MB ROM	
Built-in Functionalities		
WWAN	3.5G HSDPA/GSM/GPRS/EDGE (850, 900, 1800, 1900 and 2100MHz)	
WLAN	IEEE 802.11 b/g	
WPAN	Bluetooth v2.0 class2 with EDR	
GPS	A- GPS	
Barcode Scanner	1D Laser (2D Imager optional)	
Camera	3M pixel Autofocus with LED flash	
Others	Accelerometer	
	Digital Compass	
	User-friendly Virtual Keyboard	
Environment		
Drop	1.5m to concrete surface	
Dust & Waterproof	IP64 sealing	
Operating Temperature	-20°	C ~ + 55° C
Storage Temperature	-30°	C ~ + 70° C